



Early Journal Content on JSTOR, Free to Anyone in the World

This article is one of nearly 500,000 scholarly works digitized and made freely available to everyone in the world by JSTOR.

Known as the Early Journal Content, this set of works include research articles, news, letters, and other writings published in more than 200 of the oldest leading academic journals. The works date from the mid-seventeenth to the early twentieth centuries.

We encourage people to read and share the Early Journal Content openly and to tell others that this resource exists. People may post this content online or redistribute in any way for non-commercial purposes.

Read more about Early Journal Content at <http://about.jstor.org/participate-jstor/individuals/early-journal-content>.

JSTOR is a digital library of academic journals, books, and primary source objects. JSTOR helps people discover, use, and build upon a wide range of content through a powerful research and teaching platform, and preserves this content for future generations. JSTOR is part of ITHAKA, a not-for-profit organization that also includes Ithaka S+R and Portico. For more information about JSTOR, please contact support@jstor.org.

ON THE SPRINGFIELD RIFLE AND THE LEDUC FORMULA*

BY ARTHUR GORDON WEBSTER

CLARK UNIVERSITY, WORCESTER, MASS.

Read before the Academy, April 26, 1920

One of the formulae of interior ballistics found most useful, at any rate by practical ballisticians in the United States, is the formula of Leduc, which says that the velocity of a shot in the bore of a gun is graphically represented in terms of the distance travelled by a rectangular hyperbola, giving the formula:

$$v = \frac{as}{b + s}$$

where v is the velocity, s the distance travelled by the shot.

The writer had the curiosity to try this formula on the Springfield rifle. The observations were made by the gauge described in these PROCEEDINGS, 5, July, 1919 (259-263). The mode of deducing the Leduc formula is decidedly open to criticism since it assumes the combustion to be instantaneous, and the expansion adiabatic, neither of which is true and it is perfectly obvious that powders giving curves so different as those published in the paper quoted cannot possibly give v , s curves of the same shape. Nevertheless, it turns out that for the rifle the Leduc formula answers very well indeed.

Observations were made on the time of reaching different points in the barrel by Mr. H. C. Parker, assistant in the Ballistic Institute of Clark University. The method was to put a fine wire insulated with enamel down the barrel of the rifle to a certain distance. When the shot reached it a circuit was made which made a current passing through the oscillograph. The motion of the oscillograph was photographed on a rotating drum and thus the times were obtained. The curve obtained for the actual times of reaching ten or a dozen distances was exactly similar to that shown in the paper cited above, obtained by a double integration of the pressure-time curve. The velocities were obtained from Mr. Parker's curve by a graphic differentiation, and from the known velocities and distances the formula was obtained. Even without the method of least squares the formula $v = \frac{1133s}{19.8 + s}$ answers very well where the distances are given in centimeters and the velocities in meters per second.

* Contribution from the Ballistic Institute, No. 7.